

## **Group 9 - Brown Sliderback Cover Stock**

# Section 1. Identification

GHS product identifier	: Group 9 - Brown Sliderback Cover Stock
Product code	: 1512
Other means of identification	: Not available.
Product type	: Solid.

#### Relevant identified uses of the substance or mixture and uses advised against

entified uses
---------------

Unvulcanized Custom Mixed Rubber Compound.

Supplier's details	: Fenner Dunlop Conveyor Belting 654 Camp Joy Road, Building 2 Suite B Bluefield, Virginia 24605 USA Tel.: 276-322-1426

Emergency telephone	: CHEMTREC, U.S. : 1-800-424-9300 International: +1-703-527-3877
number (with hours of	Registration number: 8338
operation)	(24/7)

# Section 2. Hazard(s) identification

OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	: SKIN SENSITIZATION - Category 1 AQUATIC HAZARD (ACUTE) - Category 3 AQUATIC HAZARD (LONG-TERM) - Category 3
GHS label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	<ul> <li>H317 - May cause an allergic skin reaction.</li> <li>H412 - Harmful to aquatic life with long lasting effects.</li> </ul>
Precautionary statements	
Prevention	<ul> <li>P280 - Wear protective gloves.</li> <li>P273 - Avoid release to the environment.</li> <li>P261 - Avoid breathing dust.</li> <li>P272 - Contaminated work clothing should not be allowed out of the workplace.</li> </ul>
	Tel : +1-888-GHS-7769 (447-7769) / +1-450-GHS-7767 (447-7767) 1/15

rel:+1-888-GHS-7769 (447-7769) /+1-450-GHS-7767 (447-7767) www.kmkregservices.com www.askdrluc.com www.ghssmart.com



# Section 2. Hazard(s) identification

Response	<ul> <li>P362 + P364 - Take off contaminated clothing and wash it before reuse.</li> <li>P302 + P352 - IF ON SKIN: Wash with plenty of water.</li> <li>P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.</li> </ul>
Storage	: Not applicable.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazards not otherwise classified (US)	: None known.

# Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of	: Not available.
identification	

Ingredient name	% (w/w)	CAS number
Talc	7 - 13	14807-96-6
Kaolin	5 - 10	1332-58-7
Zinc oxide	1 - 5	1314-13-2
Sulfur	1 - 5	7704-34-9
Diiron trioxide	0.5 - 1.5	1309-37-1
N-cyclohexylbenzothiazole-2-sulphenamide	0.1 - 1	95-33-0

United States: The exact percentage (concentration) in the composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

Canada: The exact percentage (concentration) in the composition has been withheld as a trade secret in accordance with the amended HPR as of April 2018.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

# Section 4. First aid measures

#### **Description of necessary first aid measures**

Eye contact	<ul> <li>Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 20 minutes. Get medical attention if irritation occurs.</li> </ul>
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Wash with plenty of soap and water. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 20 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.





## Section 4. First aid measures

Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Most important sympton	ns/effects, acute and delayed

Potential acute health	effects
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/	symptoms
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No known significant effects or critical hazards.
Indication of immediate	e medical attention and special treatment needed, if necessary
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It m	nay
	be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wa	ash
	contaminated clothing thoroughly with water before removing it, or wear gloves.	

## See toxicological information (Section 11)

# Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide sulfur oxides metal oxide/oxides



# Section 5. Fire-fighting measures

Special protective actions	: Promptly isolate the scene by removing all persons from the vicinity of the incident if
for fire-fighters	there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Section 6. Accidental release measures

Personal precautions, protect	iv	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

#### Methods and materials for containment and cleaning up

Small spill	: Move containers from spill area. Avoid dust generation. Using a vacuum with HEPA filter will reduce dust dispersal. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.
Large spill	: Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

Precautions for safe handling	1	
Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.
		Tel + 1 888 CHS 7760 (447 7760) / +1 450 CHS 7767 (447 7767)

# Section 8. Exposure controls/personal protection

## **Control parameters**

## **United States**

### **Occupational exposure limits**

Ingredient name	Exposure limits
Talc Kaolin	ACGIH TLV (United States, 3/2020). TWA: 2 mg/m <sup>3</sup> 8 hours. Form: Respirable fraction NIOSH REL (United States, 10/2016). TWA: 2 mg/m <sup>3</sup> 10 hours. Form: Respirable fraction ACGIH TLV (United States, 3/2020). TWA: 2 mg/m <sup>3</sup> 8 hours. Form: Respirable fraction NIOSH REL (United States, 10/2016). TWA: 5 mg/m <sup>3</sup> 10 hours. Form: Respirable fraction TWA: 10 mg/m <sup>3</sup> 10 hours. Form: Total
	OSHA PEL (United States, 5/2018). TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Respirable fraction TWA: 15 mg/m <sup>3</sup> 8 hours. Form: Total dust
Zinc oxide	NIOSH REL (United States, 10/2016). CEIL: 15 mg/m <sup>3</sup> Form: Dust TWA: 5 mg/m <sup>3</sup> 10 hours. Form: Dust and fumes STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: Fume OSHA PEL (United States, 5/2018). TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Fume TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Respirable fraction TWA: 15 mg/m <sup>3</sup> 8 hours. Form: Total dust ACGIH TLV (United States, 3/2020). TWA: 2 mg/m <sup>3</sup> 8 hours. Form: Respirable fraction STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: Respirable fraction
Sulfur Diiron trioxide	None. NIOSH REL (United States, 10/2016). TWA: 5 mg/m <sup>3</sup> , (as Fe) 10 hours. Form: Dust and fumes OSHA PEL (United States, 5/2018). TWA: 10 mg/m <sup>3</sup> 8 hours. Form: Fume TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Respirable fraction TWA: 15 mg/m <sup>3</sup> 8 hours. Form: Total dust ACGIH TLV (United States, 3/2020). TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Respirable fraction
N-cyclohexylbenzothiazole-2-sulphenamide	None.

#### Canada

#### **Occupational exposure limits**



Group 9 - Brown Sliderback Cover Stock

# Section 8. Exposure controls/personal protection

Ingredient name	Exposure limits
Talc	<ul> <li>CA Quebec Provincial (Canada, 7/2019). TWAEV: 3 mg/m<sup>3</sup> 8 hours. Form: Respirable dust</li> <li>CA Saskatchewan Provincial (Canada, 7/2013). TWA: 2 mg/m<sup>3</sup> 8 hours. Form: Respirable fraction</li> <li>CA Ontario Provincial (Canada, 6/2019). TWA: 2 mg/m<sup>3</sup> 8 hours. Form: Respirable particulate matter TWA: 2 f/cc 8 hours.</li> <li>CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 2 mg/m<sup>3</sup> 8 hours. Form: Respirable particulate.</li> <li>CA British Columbia Provincial (Canada, 1/2020). TWA: 2 mg/m<sup>3</sup> 8 hours. Form: Respirable</li> </ul>
Kaolin	<ul> <li>TWA: 2 mg/m<sup>3</sup> 8 hours. Form: Respirable.</li> <li>CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 2 mg/m<sup>3</sup> 8 hours. Form: Respirable</li> <li>CA British Columbia Provincial (Canada, 1/2020).</li> <li>TWA: 2 mg/m<sup>3</sup> 8 hours. Form: Respirable</li> <li>CA Quebec Provincial (Canada, 7/2019).</li> <li>TWAEV: 5 mg/m<sup>3</sup> 8 hours. Form: Respirable dust</li> <li>CA Saskatchewan Provincial (Canada, 7/2013).</li> <li>STEL: 4 mg/m<sup>3</sup> 15 minutes. Form: Respirable fraction</li> <li>TWA: 2 mg/m<sup>3</sup> 8 hours. Form: Respirable fraction</li> </ul>
Zinc oxide	particulate matter <b>CA Alberta Provincial (Canada, 6/2018).</b> 8 hrs OEL: 2 mg/m <sup>3</sup> 8 hours. Form: Respirable 15 min OEL: 10 mg/m <sup>3</sup> 15 minutes. Form: Respirable <b>CA British Columbia Provincial (Canada,</b> <b>1/2020).</b> TWA: 2 mg/m <sup>3</sup> 8 hours. Form: Respirable STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: Respirable <b>CA Ontario Provincial (Canada, 6/2019).</b> TWA: 2 mg/m <sup>3</sup> 8 hours. Form: Respirable particulate matter. STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: Respirable particulate matter. <b>CA Quebec Provincial (Canada, 7/2019).</b> TWAEV: 5 mg/m <sup>3</sup> 8 hours. Form: fume STEV: 10 mg/m <sup>3</sup> 15 minutes. Form: fume

Tel : +1-888-GHS-7769 (447-7769) / +1-450-GHS-7767 (447-7767) www.kmkregservices.com www.askdrluc.com www.ghssmart.com



# Section 8. Exposure controls/personal protection

7/2013).         STEL: 10 mg/m³ 15 minutes. Form:         respirable dust and fume         TWA: 2 mg/m³ 8 hours. Form: respiratust and fume         CA Alberta Provincial (Canada, 6/20         8 hrs OEL: 10 mg/m³ 8 hours.         Diiron trioxide         Diiron trioxide         CA British Columbia Provincial (Canada, 6/20).         TWA: 5 mg/m³, (as Fe) 8 hours. Form:         TWA: 5 mg/m³, (as Fe) 8 hours. Form:         Stel: 10 mg/m³ 8 hours. Form: TWA: 5 mg/m³, (as Fe) 15 minutes         Fume         TWA: 10 mg/m³ 8 hours. Form: Tota         CA Ontario Provincial (Canada, 6/20         TWA: 5 mg/m³ 8 hours. Form: Respi         particulate matter         CA Alberta Provincial (Canada, 7/20         TWA: 5 mg/m³ 8 hours. Form:         Respirable.         CA Quebec Provincial (Canada, 7/20         TWAEV: 5 mg/m³, (as Fe) 8 hours. Form:         Respirable.         CA Quebec Provincial (Canada, 7/20         TWAEV: 5 mg/m³, (as Fe) 8 hours. Form:         dust and fume         CA Saskatchewan Provincial (Canada, 7/20         TWAEV: 5 mg/m³, (measured as Fe)         minutes. Form: dust and fume			· · · · · ·
SulfurSTEL: 10 mg/m³ 15 minutes. Form: respirable dust and fume TWA: 2 mg/m³ 8 hours. Form: respira dust and fumeDiiron trioxideCA Alberta Provincial (Canada, 6/20 8 hrs OEL: 10 mg/m³ 8 hours.Diiron trioxideCA Alberta Provincial (Canada, 6/20 9 hrs OEL: 10 mg/m³ 8 hours.Diiron trioxideCA Birtish Columbia Provincial (Canada, 6/20). TWA: 5 mg/m³, (as Fe) 8 hours. Form: TWA: 5 mg/m³, (as Fe) 8 hours. Form: STEL: 10 mg/m³ 8 hours. Form: Tota CA Ontario Provincial (Canada, 6/20) TWA: 5 mg/m³ 8 hours. Form: Respi particulate matterCA Alberta Provincial (Canada, 6/20) 8 hrs OEL: 5 mg/m³ 8 hours. Form: Respi particulate matterCA Alberta Provincial (Canada, 6/20) 8 hrs OEL: 5 mg/m³ 8 hours. Form: Respirable.CA Quebec Provincial (Canada, 7/20) TWAEV: 5 mg/m³ (as Fe) 8 hours. F dust and fume CA Saskatchewan Provincial (Canada, 7/20) TWAEV: 5 mg/m³, (measured as Fe) 8 minutes. Form: dust and fume TWA: 5 mg/m³, (measured as Fe) 8	ada,	CA Saskatchewan Provincial (Canada,	
sulfur CA Alberta Provincial (Canada, 6/20 8 hrs OEL: 10 mg/m³ 8 hours. Form: respira dust and fume CA Alberta Provincial (Canada, 6/20 8 hrs OEL: 10 mg/m³ 8 hours. CA British Columbia Provincial (Can 1/2020). TWA: 5 mg/m³, (as Fe) 8 hours. Forr TWA: 5 mg/m³, (as Fe) 8 hours. Forr STEL: 10 mg/m³ 8 hours. Forr: Tota CA Ontario Provincial (Canada, 6/20 TWA: 10 mg/m³ 8 hours. Form: Tota CA Alberta Provincial (Canada, 6/20 TWA: 5 mg/m³ 8 hours. Form: Respi particulate matter CA Alberta Provincial (Canada, 6/20 8 hrs OEL: 5 mg/m³ 8 hours. Form: Respirable. CA Quebec Provincial (Canada, 7/20 TWAEV: 5 mg/m³, (as Fe) 8 hours. Form: dust and fume CA Saskatchewan Provincial (Canada, 7/20 TVAES. 5 mg/m³, (measured as Fe) 7 minutes. Form: dust and fume TWA: 5 mg/m³, (measured as Fe) 8 hours.		,	
TWA: 2 mg/m³ 8 hours. Form: respiradust and fume         Sulfur       CA Alberta Provincial (Canada, 6/20 8 hrs OEL: 10 mg/m³ 8 hours.         Diiron trioxide       CA British Columbia Provincial (Canada, 1/2020).         TWA: 5 mg/m³, (as Fe) 8 hours. Forr       TWA: 5 mg/m³, (as Fe) 8 hours. Forr         STEL: 10 mg/m³, (as Fe) 15 minutes       Fume         TWA: 10 mg/m³ 8 hours. Form: Tota       CA Ontario Provincial (Canada, 6/20         TWA: 5 mg/m³ 8 hours. Form: Respirable.       CA Alberta Provincial (Canada, 6/20         8 hrs OEL: 5 mg/m³ 8 hours. Form: Respirable.       CA Quebec Provincial (Canada, 7/20         TWAEV: 5 mg/m³, (as Fe) 8 hours. Forr:       Respirable.         CA Saskatchewan Provincial (Canada, 7/20       TWAEV: 5 mg/m³, (as Fe) 8 hours. Forr:         Rust and fume       CA Saskatchewan Provincial (Canada, 7/20         TWAEV: 5 mg/m³, (measured as Fe) 7       minutes. Forr: dust and fume         TWAEV: 5 mg/m³, (measured as Fe) 8       STEL: 10 mg/m³, (measured as Fe) 7	:		
Sulfur       CA Alberta Provincial (Canada, 6/20 8 hrs OEL: 10 mg/m³ 8 hours.         Diiron trioxide       CA British Columbia Provincial (Canada, 1/2020).         TWA: 5 mg/m³, (as Fe) 8 hours. Forr       TWA: 5 mg/m³, (as Fe) 8 hours. Forr         STEL: 10 mg/m³, (as Fe) 15 minutes       Fume         TWA: 10 mg/m³ 8 hours. Form: Tota       CA Ontario Provincial (Canada, 6/20)         TWA: 5 mg/m³ 8 hours. Form: Respiparticulate matter       CA Alberta Provincial (Canada, 6/20)         CA Alberta Provincial (Canada, 6/20)       8 hrs OEL: 5 mg/m³ 8 hours. Form: Respiparticulate matter         CA Quebec Provincial (Canada, 7/20)       TWAEV: 5 mg/m³, (as Fe) 8 hours. Form:         Respirable.       CA Quebec Provincial (Canada, 7/20)         STEL: 10 mg/m³, (measured as Fe) 7       minutes. Form: dust and fume         TWA: 5 mg/m³, (measured as Fe) 7       minutes. Form: dust and fume         TWA: 5 mg/m³, (measured as Fe) 8       Minutes. Form: dust and fume			
Sulfur       CA Alberta Provincial (Canada, 6/20 8 hrs OEL: 10 mg/m³ 8 hours.         Diiron trioxide       CA British Columbia Provincial (Canada, 1/2020). TWA: 5 mg/m³, (as Fe) 8 hours. Forr TWA: 5 mg/m³, (as Fe) 8 hours. Forr STEL: 10 mg/m³, (as Fe) 15 minutes Fume TWA: 10 mg/m³ 8 hours. Form: Tota CA Ontario Provincial (Canada, 6/20 TWA: 5 mg/m³ 8 hours. Form: Respi particulate matter CA Alberta Provincial (Canada, 6/20 8 hrs OEL: 5 mg/m³ 8 hours. Form: Respi particulate matter CA Alberta Provincial (Canada, 6/20 8 hrs OEL: 5 mg/m³ 8 hours. Form: Respi particulate matter CA Alberta Provincial (Canada, 7/20 TWAEV: 5 mg/m³, (as Fe) 8 hours. Form: Respirable.         CA Quebec Provincial (Canada, 7/20 TWAEV: 5 mg/m³, (as Fe) 8 hours. Form: dust and fume CA Saskatchewan Provincial (Canada, 7/2013). STEL: 10 mg/m³, (measured as Fe) 8	virable	TWA: 2 mg/m <sup>3</sup> 8 hours. Form: respirable	
Birs OEL: 10 mg/m³ 8 hours.         Diiron trioxide         CA British Columbia Provincial (Can         1/2020).         TWA: 5 mg/m³, (as Fe) 8 hours. Forr         STEL: 10 mg/m³, (as Fe) 15 minutes         Fume         TWA: 10 mg/m³ 8 hours. Form: Tota         CA Ontario Provincial (Canada, 6/20         TWA: 5 mg/m³ 8 hours. Form: Respi         particulate matter         CA Alberta Provincial (Canada, 6/20         8 hrs OEL: 5 mg/m³ 8 hours. Form: Respi         particulate matter         CA Quebec Provincial (Canada, 7/20         TWAEV: 5 mg/m³, (as Fe) 8 hours. Form:         Respirable.         CA Saskatchewan Provincial (Canada, 7/20         TWAEV: 5 mg/m³, (measured as Fe) 7         minutes. Form: dust and fume         TWA: 5 mg/m³, (measured as Fe) 8		dust and fume	
B hrs OEL: 10 mg/m³ 8 hours.         Diiron trioxide         B hrs OEL: 10 mg/m³ 8 hours.         CA British Columbia Provincial (Can 1/2020).         TWA: 5 mg/m³, (as Fe) 8 hours. Forr TWA: 5 mg/m³, (as Fe) 15 minutes         Fume         TWA: 10 mg/m³ 8 hours. Form: Tota         CA Ontario Provincial (Canada, 6/20)         TWA: 5 mg/m³ 8 hours. Form: Respirable.         CA Alberta Provincial (Canada, 7/20)         8 hrs OEL: 5 mg/m³, (as Fe) 8 hours. Form: Respirable.         CA Quebec Provincial (Canada, 7/20)         TWAEV: 5 mg/m³, (as Fe) 8 hours. Form: Respirable.         CA Saskatchewan Provincial (Canada, 7/20)         STEL: 10 mg/m³, (measured as Fe) 7 minutes. Form: dust and fume         TWA: 5 mg/m³, (measured as Fe) 8   7	2018).	CA Alberta Provincial (Canada, 6/2018).	Sulfur
<ul> <li>1/2020).</li> <li>TWA: 5 mg/m³, (as Fe) 8 hours. Forr TWA: 5 mg/m³, (as Fe) 15 minutes Fume</li> <li>TWA: 10 mg/m³ 8 hours. Form: Tota</li> <li>CA Ontario Provincial (Canada, 6/20 TWA: 5 mg/m³ 8 hours. Form: Respi particulate matter</li> <li>CA Alberta Provincial (Canada, 6/20 8 hrs OEL: 5 mg/m³ 8 hours. Form: Respirable.</li> <li>CA Quebec Provincial (Canada, 7/20 TWAEV: 5 mg/m³, (as Fe) 8 hours. Form: Respirable.</li> <li>CA Quebec Provincial (Canada, 7/20 TWAEV: 5 mg/m³, (as Fe) 8 hours. Form: dust and fume</li> <li>CA Saskatchewan Provincial (Canada 7/2013).</li> <li>STEL: 10 mg/m³, (measured as Fe) 7 minutes. Form: dust and fume</li> <li>TWA: 5 mg/m³, (measured as Fe) 8 log</li> </ul>			
TWA: 5 mg/m³, (as Fe) 8 hours. Forr TWA: 5 mg/m³, (as Fe) 15 minutes Fume TWA: 10 mg/m³ 8 hours. Form: Tota <b>CA Ontario Provincial (Canada, 6/20</b> TWA: 5 mg/m³ 8 hours. Form: Respi particulate matter <b>CA Alberta Provincial (Canada, 6/20</b> 8 hrs OEL: 5 mg/m³ 8 hours. Form: Respirable. <b>CA Quebec Provincial (Canada, 7/20</b> TWAEV: 5 mg/m³, (as Fe) 8 hours. F dust and fume <b>CA Saskatchewan Provincial (Canada, 7/20</b> T/2013). STEL: 10 mg/m³, (measured as Fe) 8	anada,	CA British Columbia Provincial (Canada	Diiron trioxide
TWA: 5 mg/m³, (as Fe) 8 hours. Forr STEL: 10 mg/m³, (as Fe) 15 minutes Fume TWA: 10 mg/m³ 8 hours. Form: Tota <b>CA Ontario Provincial (Canada, 6/20</b> TWA: 5 mg/m³ 8 hours. Form: Respi particulate matter <b>CA Alberta Provincial (Canada, 6/20</b> 8 hrs OEL: 5 mg/m³ 8 hours. Form: Respirable. <b>CA Quebec Provincial (Canada, 7/20</b> TWAEV: 5 mg/m³, (as Fe) 8 hours. F dust and fume <b>CA Saskatchewan Provincial (Canada, 7/20</b> T/2013). STEL: 10 mg/m³, (measured as Fe) 7 minutes. Form: dust and fume TWA: 5 mg/m³, (measured as Fe) 8		1/2020).	
<ul> <li>TWA: 5 mg/m³, (as Fe) 8 hours. Forr STEL: 10 mg/m³, (as Fe) 15 minutes Fume TWA: 10 mg/m³ 8 hours. Form: Tota CA Ontario Provincial (Canada, 6/20 TWA: 5 mg/m³ 8 hours. Form: Respi particulate matter CA Alberta Provincial (Canada, 6/20 8 hrs OEL: 5 mg/m³ 8 hours. Form: Respirable.</li> <li>CA Quebec Provincial (Canada, 7/20 TWAEV: 5 mg/m³, (as Fe) 8 hours. F dust and fume CA Saskatchewan Provincial (Canada, 7/20 T/2013). STEL: 10 mg/m³, (measured as Fe) 8</li> </ul>	orm: Dust	TWA: 5 mg/m <sup>3</sup> , (as Fe) 8 hours. Form: Du	
STEL: 10 mg/m³, (as Fe) 15 minutes Fume TWA: 10 mg/m³ 8 hours. Form: Tota <b>CA Ontario Provincial (Canada, 6/20</b> TWA: 5 mg/m³ 8 hours. Form: Respi particulate matter <b>CA Alberta Provincial (Canada, 6/20</b> 8 hrs OEL: 5 mg/m³ 8 hours. Form: Respirable. <b>CA Quebec Provincial (Canada, 7/20</b> TWAEV: 5 mg/m³, (as Fe) 8 hours. F dust and fume <b>CA Saskatchewan Provincial (Canada</b> <b>7/2013).</b> STEL: 10 mg/m³, (measured as Fe) 7 minutes. Form: dust and fume TWA: 5 mg/m³, (measured as Fe) 8 hours.		TWA: 5 mg/m <sup>3</sup> , (as Fe) 8 hours. Form: Fu	
TWA: 10 mg/m <sup>3</sup> 8 hours. Form: Tota <b>CA Ontario Provincial (Canada, 6/20</b> TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Respi particulate matter <b>CA Alberta Provincial (Canada, 6/20</b> 8 hrs OEL: 5 mg/m <sup>3</sup> 8 hours. Form: Respirable. <b>CA Quebec Provincial (Canada, 7/20</b> TWAEV: 5 mg/m <sup>3</sup> , (as Fe) 8 hours. F dust and fume <b>CA Saskatchewan Provincial (Canada</b> <b>7/2013).</b> STEL: 10 mg/m <sup>3</sup> , (measured as Fe) 7 minutes. Form: dust and fume TWA: 5 mg/m <sup>3</sup> , (measured as Fe) 8	es. Form:	STEL: 10 mg/m <sup>3</sup> , (as Fe) 15 minutes. For	
CA Ontario Provincial (Canada, 6/20 TWA: 5 mg/m³ 8 hours. Form: Respi particulate matterCA Alberta Provincial (Canada, 6/20 8 hrs OEL: 5 mg/m³ 8 hours. Form: Respirable.CA Quebec Provincial (Canada, 7/20 TWAEV: 5 mg/m³, (as Fe) 8 hours. F dust and fumeCA Saskatchewan Provincial (Canada T/2013). STEL: 10 mg/m³, (measured as Fe) 7 minutes. Form: dust and fume TWA: 5 mg/m³, (measured as Fe) 8 hours.		Fume	
TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Respin particulate matter <b>CA Alberta Provincial (Canada, 6/20</b> 8 hrs OEL: 5 mg/m <sup>3</sup> 8 hours. Form: Respirable. <b>CA Quebec Provincial (Canada, 7/20</b> TWAEV: 5 mg/m <sup>3</sup> , (as Fe) 8 hours. F dust and fume <b>CA Saskatchewan Provincial (Canada</b> <b>7/2013).</b> STEL: 10 mg/m <sup>3</sup> , (measured as Fe) 7 minutes. Form: dust and fume TWA: 5 mg/m <sup>3</sup> , (measured as Fe) 8		TWA: 10 mg/m <sup>3</sup> 8 hours. Form: Total dus	
particulate matter <b>CA Alberta Provincial (Canada, 6/20</b> 8 hrs OEL: 5 mg/m <sup>3</sup> 8 hours. Form: Respirable. <b>CA Quebec Provincial (Canada, 7/20</b> TWAEV: 5 mg/m <sup>3</sup> , (as Fe) 8 hours. F dust and fume <b>CA Saskatchewan Provincial (Canada)</b> <b>7/2013).</b> STEL: 10 mg/m <sup>3</sup> , (measured as Fe) 7 minutes. Form: dust and fume TWA: 5 mg/m <sup>3</sup> , (measured as Fe) 8	2019).	CA Ontario Provincial (Canada, 6/2019).	
CA Alberta Provincial (Canada, 6/20 8 hrs OEL: 5 mg/m <sup>3</sup> 8 hours. Form: Respirable. CA Quebec Provincial (Canada, 7/20 TWAEV: 5 mg/m <sup>3</sup> , (as Fe) 8 hours. F dust and fume CA Saskatchewan Provincial (Canada 7/2013). STEL: 10 mg/m <sup>3</sup> , (measured as Fe) 7 minutes. Form: dust and fume TWA: 5 mg/m <sup>3</sup> , (measured as Fe) 8	pirable	TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Respirable	
8 hrs OEL: 5 mg/m <sup>3</sup> 8 hours. Form: Respirable. <b>CA Quebec Provincial (Canada, 7/20</b> TWAEV: 5 mg/m <sup>3</sup> , (as Fe) 8 hours. F dust and fume <b>CA Saskatchewan Provincial (Canada</b> <b>7/2013).</b> STEL: 10 mg/m <sup>3</sup> , (measured as Fe) 7 minutes. Form: dust and fume TWA: 5 mg/m <sup>3</sup> , (measured as Fe) 8			
Respirable. <b>CA Quebec Provincial (Canada, 7/20</b> TWAEV: 5 mg/m³, (as Fe) 8 hours. F dust and fume <b>CA Saskatchewan Provincial (Canada)</b> <b>7/2013).</b> STEL: 10 mg/m³, (measured as Fe) 7 minutes. Form: dust and fume TWA: 5 mg/m³, (measured as Fe) 8 l	,	CA Alberta Provincial (Canada, 6/2018).	
CA Quebec Provincial (Canada, 7/20 TWAEV: 5 mg/m³, (as Fe) 8 hours. F dust and fume CA Saskatchewan Provincial (Canada 7/2013). STEL: 10 mg/m³, (measured as Fe) 7 minutes. Form: dust and fume TWA: 5 mg/m³, (measured as Fe) 8 l			
TWAEV: 5 mg/m³, (as Fe) 8 hours. F dust and fume <b>CA Saskatchewan Provincial (Cana</b> <b>7/2013).</b> STEL: 10 mg/m³, (measured as Fe) 7 minutes. Form: dust and fume TWA: 5 mg/m³, (measured as Fe) 8			
dust and fume <b>CA Saskatchewan Provincial (Cana</b> <b>7/2013).</b> STEL: 10 mg/m³, (measured as Fe) 7 minutes. Form: dust and fume TWA: 5 mg/m³, (measured as Fe) 8	,	CA Quebec Provincial (Canada, 7/2019).	
<b>CA Saskatchewan Provincial (Cana</b> <b>7/2013).</b> STEL: 10 mg/m³, (measured as Fe) <sup>7</sup> minutes. Form: dust and fume TWA: 5 mg/m³, (measured as Fe) 8	Form:	TWAEV: 5 mg/m <sup>3</sup> , (as Fe) 8 hours. Form:	
<b>7/2013).</b> STEL: 10 mg/m³, (measured as Fe) 7 minutes. Form: dust and fume TWA: 5 mg/m³, (measured as Fe) 8			
STEL: 10 mg/m³, (measured as Fe) f minutes. Form: dust and fume TWA: 5 mg/m³, (measured as Fe) 8	ada,		
minutes. Form: dust and fume TWA: 5 mg/m³, (measured as Fe) 8 l			
TWA: 5 mg/m³, (measured as Fe) 8	) 15	STEL: 10 mg/m³, (measured as Fe) 15	
Form: dust and fume	3 hours.	TWA: 5 mg/m <sup>3</sup> , (measured as Fe) 8 hours	
		Form: dust and fume	

Appropriate engineering controls	: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.	
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.	

## Individual protection measures

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

#### **Skin protection**



# Section 8. Exposure controls/personal protection

Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

# Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance		
Physical state	:	Solid. [Opaque.]
Color	:	Brown.
Odor	:	None.
Odor threshold	:	Not available.
рН	:	Not available.
Melting point/freezing point	:	Not available.
Boiling point, initial boiling point, and boiling range	:	Not available.
Flash point	:	Not applicable.
Evaporation rate	:	Not available.
Flammability	:	Not available.
Lower and upper explosion limit/flammability limit	:	Not applicable.
Vapor pressure	:	Not available.
Relative vapor density	:	Not applicable.
Relative density	:	Not available.
Solubility	:	Not available.
Solubility in water	:	Not available.
Miscible with water	:	Not available.
Partition coefficient: n- octanol/water	:	Not applicable.
Auto-ignition temperature	:	Not applicable.
Decomposition temperature	1	Not available.
Viscosity	:	Not applicable.
Flow time (ISO 2431)	:	Not available.
Particle characteristics		

Particle characteristics



Tel : +1-888-GHS-7769 (447-7769) / +1-450-GHS-7767 (447-7767) www.kmkregservices.com www.askdrluc.com www.ghssmart.com

## <u>FENNER 🔶 DUNLOP</u>

# Section 9. Physical and chemical properties and safety characteristics

Median particle size : Not available.

# Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

## Information on toxicological effects

## Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
N-cyclohexylbenzothiazole- 2-sulphenamide	LD50 Dermal	Rabbit	>7940 mg/kg	-
	LD50 Oral	Rat	5300 mg/kg	-

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Talc	Skin - Mild irritant	Human	-	72 hours 300	-
N-cyclohexylbenzothiazole- 2-sulphenamide	Eyes - Mild irritant	Rabbit	-	µg Intermittent 100 %	-
	Skin - Mild irritant	Rabbit	-	100 %	-

#### **Sensitization**

There is no data available.

## **Mutagenicity**

There is no data available.

#### **Carcinogenicity**

## **Classification United States**

Product/ingredient name	OSHA	IARC	NTP
Talc Diiron trioxide	-	3 3	-

**Classification Canada** 



# Section 11. Toxicological information

Product/ingredient name	IARC	NTP	ACGIH
Talc	3	-	A4
Kaolin	-	-	A4
Diiron trioxide	3	-	A4

## **Reproductive toxicity**

There is no data available.

## **Teratogenicity**

There is no data available.

#### Specific target organ toxicity (single exposure)

There is no data available.

#### Specific target organ toxicity (repeated exposure)

There is no data available.

#### **Aspiration hazard**

There is no data available.

Information on the likely routes of exposure	: Routes of entry anticipated: Oral, Dermal, Inhalation.
Potential acute health effec	ts
Eye contact	No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the ph	sysical, chemical and toxicological characteristics
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No known significant effects or critical hazards.
Delayed and immediate effe	ects and also chronic effects from short and long term exposure
<u>Short term exposure</u>	
Potential immediate effects	: No known significant effects or critical hazards.
Potential delayed effects	: No known significant effects or critical hazards.
Long term exposure	
Potential immediate effects	: No known significant effects or critical hazards.
Potential delayed effects	: No known significant effects or critical hazards.
Potential chronic health eff	ects
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
	Tel : +1-888-GHS-7769 (447-7769) / +1-450-GHS-7767 (447-7767) <b>10</b>

www.kmkregservices.com www.askdrluc.com www.ghssmart.com

## <u>FENNER 🔶 DUNLOP</u>

# Section 11. Toxicological information

Mutagenicity Reproductive toxicity : No known significant effects or critical hazards.

**toxicity** : No known significant effects or critical hazards.

## Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name		Dermal (mg/kg)		(vapors)	Inhalation (dusts and mists) (mg/ I)
N-cyclohexylbenzothiazole-2-sulphenamide	5300	N/A	N/A	N/A	N/A

# Section 12. Ecological information

## **Toxicity**

Product/ingredient name	Result	Species	Exposure
Zinc oxide	Acute IC50 1.85 mg/L Marine water Acute IC50 46 μg/L Fresh water	Algae - Skeletonema costatum Algae - Pseudokirchneriella subcapitata - Exponential growth phase	96 hours 72 hours
	Acute LC50 98 µg/L Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
Sulfur	Acute LC50 1.1 ppm Fresh water Acute LC50 >100 ppm Fresh water	Fish - Oncorhynchus mykiss Fish - Oncorhynchus mykiss	96 hours 96 hours

## Persistence and degradability

There is no data available.

## **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Zinc oxide N-cyclohexylbenzothiazole- 2-sulphenamide	- 5	28960 -	high high

#### Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.





# Section 13. Disposal considerations

**Disposal methods** 

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

	DOT Classification	TDG Classification	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-
Transport hazard class(es)	-	-	-	-
Packing group	-	-	-	-
Environmental hazards	No.	No.	No.	No.

**AERG** : Not applicable

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to IMO instruments

# Section 15. Regulatory information

U.S. Federal regulations	: TSCA 6 proposed risk management: Lead TSCA 8(a) CDR Exempt/Partial exemption: Not determined
	<b>Clean Water Act (CWA) 307</b> : Zinc oxide; Cadmium Oxide; Lead Monoxide; Lead; Cadmium (Non-pyrophoric)
	Clean Water Act (CWA) 311: p-Cresol
Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	: Listed
Clean Air Act Section 602 Class I Substances	: Not listed



Tel : +1-888-GHS-7769 (447-7769) / +1-450-GHS-7767 (447-7767) www.kmkregservices.com www.askdrluc.com www.ghssmart.com



## Section 15. Regulatory information

Clean Air Act Section 602 Class II Substances	: Not listed
DEA List I Chemicals (Precursor Chemicals)	: Not listed
DEA List II Chemicals (Essential Chemicals)	: Not listed

#### SARA 302/304

#### Composition/information on ingredients

			SARA 302 TPQ SARA 304 RQ		Q	
Name	%	EHS	(lbs)	(gallons)	(lbs)	(gallons)
Cadmium Oxide	<0.01	Yes.	100 / 10000	-	100	-

SARA 304 RQ

: 1330672 lbs / 604125.1 kg

## SARA 311/312

Classification : SKIN SENSITIZATION - Category 1

#### Composition/information on ingredients

Name	%	Classification
Sulfur		FLAMMABLE SOLIDS - Category 2 SKIN CORROSION/IRRITATION - Category 2
N-cyclohexylbenzothiazole- 2-sulphenamide		SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2B SKIN SENSITIZATION - Category 1

#### SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	Zinc oxide	1314-13-2	≥3 - ≤5
Supplier notification	Zinc oxide	1314-13-2	≥3 - ≤5

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

#### State regulations

Massachusetts	: The following components are listed: Talc; Kaolin; Zinc oxide; Sulfur; Diiron trioxide
New York	: None of the components are listed.
New Jersey	<ul> <li>The following components are listed: Talc; Kaolin; Zinc oxide; Sulfur; Diiron trioxide; Carbon black, non respirable</li> </ul>
Pennsylvania	: The following components are listed: Talc; Kaolin; Zinc oxide; Sulfur; Diiron trioxide

#### California Prop. 65

▲ WARNING: This product can expose you to chemicals including Cadmium Oxide, Lead and Cadmium (Non-pyrophoric), which are known to the State of California to cause cancer and birth defects or other reproductive harm. This product can expose you to chemicals including Lead Monoxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.





# Section 15. Regulatory information

Ingredient name	No significant risk level	Maximum acceptable dosage level
Cadmium Oxide	-	-
Lead Monoxide	-	-
Lead	Yes.	Yes.
Cadmium (Non-pyrophoric)	Yes.	Yes.

#### **Canadian lists**

#### Canadian NPRI

: The following components are listed: Zinc oxide **CEPA Toxic substances** 

: None of the components are listed.

## **International regulations**

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

## Montreal Protocol

Not listed.

## Stockholm Convention on Persistent Organic Pollutants

Not listed.

## Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

## **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

#### **Inventory list**

Canada

: At least one component is not listed in DSL but all such components are listed in NDSL.

**United States (TSCA 8b)** : All components are active or exempted.

## Section 16. Other information

#### Procedure used to derive the classification

Classification	Justification
AQUATIC HAZARD (ACUTE) - Category 3	Calculation method Calculation method Calculation method

<u>History</u>	
Date of issue/Date of revision	: 09/15/2021
Date of previous issue	: 11/30/2018
Version	: 7
Prepared by	: KMK Regulatory Services Inc.





# Section 16. Other information

Key to abbreviations	: ATE = Acute Toxicity Estimate
	BCF = Bioconcentration Factor
	GHS = Globally Harmonized System of Classification and Labelling of Chemicals
	IATA = International Air Transport Association
	IBC = Intermediate Bulk Container
	IMDG = International Maritime Dangerous Goods
	LogPow = logarithm of the octanol/water partition coefficient
	MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
	N/A = Not available
	SGG = Segregation Group
	UN = United Nations

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

