

## SAFETY DATA SHEET

**Premium Range Tie Gum (Group 1,2,7,8,10 & 12)** 

## **Section 1. Identification**

GHS product identifier : Premium Range Tie Gum (Group 1,2,7,8,10 & 12)

Product code : 3024

Other means of : Not available. identification

Product type : Solid.

#### Relevant identified uses of the substance or mixture and uses advised against

#### **Identified uses**

Unvulcanized Custom Mixed Rubber Compound.

Supplier's details : Fenner Dunlop Conveyor Belting

654 Camp Joy Road, Building 2 Suite B

Bluefield, Virginia 24605

USA

Tel.: 276-322-1426

Emergency telephone number (with hours of

operation)

: CHEMTREC, U.S.: 1-800-424-9300 International: +1-703-527-3877

Registration number: 8338

(24/7)

## Section 2. Hazard(s) identification

**OSHA/HCS** status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture

: SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 1

TOXIC TO REPRODUCTION - Category 1
AQUATIC HAZARD (ACUTE) - Category 2
AQUATIC HAZARD (LONG-TERM) - Category 2

#### **GHS** label elements

Hazard pictograms







Signal word : Danger

**Hazard statements**: H317 - May cause an allergic skin reaction.

H350 - May cause cancer.

H360 - May damage fertility or the unborn child. H411 - Toxic to aquatic life with long lasting effects.

#### **Precautionary statements**





## Section 2. Hazard(s) identification

**Prevention**: P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P280 - Wear protective gloves, protective clothing and eye or face protection.

P273 - Avoid release to the environment.

P261 - Avoid breathing dust.

P272 - Contaminated work clothing should not be allowed out of the workplace.

Response : P391 - Collect spillage.

P308 + P313 - IF exposed or concerned: Get medical advice or attention.

P362 + P364 - Take off contaminated clothing and wash it before reuse.

P302 + P352 - IF ON SKIN: Wash with plenty of water.

P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.

Storage : P405 - Store locked up.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national

and international regulations.

Hazards not otherwise classified (US)

: None known.

## Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Other means of identification

Not available.

Ingredient name	% (w/w)	CAS number
Carbon black	10 - 30	1333-86-4
Silica gel, pptd., crystfree	10 - 30	112926-00-8
Extracts (Petroleum), Heavy Paraffinic Distillate Solvent	5 - 10	64742-04-7
Zinc oxide	1 - 5	1314-13-2
Sulfur, homopolymer	1 - 5	9035-99-8
Resorcinol Formaldehyde Resin	1 - 5	65876-95-1
N-1,3-Dimethylbutyl-N'-Phenyl-P-Phenylenediamine	0.1 - 1	793-24-8
2-(Morpholinothio)Benzothiazole	0.1 - 1	102-77-2
di(Benzothiazol-2-yl) Disulphide	0.1 - 1	120-78-5
Resorcinol	0.1 - 1	108-46-3
Neodecanoic acid, cobalt salt	0.1 - 1	27253-31-2

United States: The exact percentage (concentration) in the composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

Canada: The exact percentage (concentration) in the composition has been withheld as a trade secret in accordance with the amended HPR as of April 2018.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

#### **Description of necessary first aid measures**

**Eye contact** 

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 20 minutes. Get medical attention.



### Section 4. First aid measures

#### Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Skin contact

: Wash with plenty of soap and water. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 20 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

#### Ingestion

Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

**Skin contact**: May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

Eye contactInhalationNo known significant effects or critical hazards.Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

**Skin contact**: Adverse symptoms may include the following:

irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

**Ingestion** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments

: No specific treatment.

**Protection of first-aiders** 

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.



### Section 4. First aid measures

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

#### **Extinguishing media**

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media

: None known.

Specific hazards arising from the chemical

: This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products

 Decomposition products may include the following materials: carbon dioxide carbon monoxide sulfur oxides metal oxide/oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

#### Methods and materials for containment and cleaning up

**Small spill** 

: Move containers from spill area. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

Large spill

: Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.





## Section 7. Handling and storage

#### **Precautions for safe handling**

#### **Protective measures**

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

## Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures.

# Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

#### **Control parameters**

**United States** 

Occupational exposure limits

Ingredient name	Exposure limits
Carbon black	ACGIH TLV (United States, 3/2020).
	TWA: 3 mg/m³ 8 hours. Form: Inhalable
	fraction
	NIOSH REL (United States, 10/2016).
	TWA: 3.5 mg/m³ 10 hours.
	TWA: 0.1 mg of PAHs/cm³ 10 hours.
	OSHA PEL (United States, 5/2018).
	TWA: 3.5 mg/m³ 8 hours.
Silica gel, pptd., crystfree	NIOSH REL (United States, 10/2016).
	TWA: 6 mg/m³ 10 hours.
Extracts (Petroleum), Heavy Paraffinic Distillate Solvent	NIOSH REL (United States, 10/2016).
	TWA: 5 mg/m³ 10 hours. Form: Mist
Zina avida	STEL: 10 mg/m³ 15 minutes. Form: Mist
Zinc oxide	NIOSH REL (United States, 10/2016).
	CEIL: 15 mg/m³ Form: Dust
	TWA: 5 mg/m³ 10 hours. Form: Dust and fumes
	STEL: 10 mg/m³ 15 minutes. Form: Fume
	OSHA PEL (United States, 5/2018).
	TWA: 5 mg/m³ 8 hours. Form: Fume
	TWA: 5 mg/m³ 8 hours. Form: Respirable
	fraction
	TWA: 15 mg/m³ 8 hours. Form: Total dust



## Section 8. Exposure controls/personal protection

ACGIH TLV (United States, 3/2020). TWA: 2 mg/m<sup>3</sup> 8 hours. Form: Respirable fraction STEL: 10 mg/m<sup>3</sup> 15 minutes. Form: Respirable fraction Sulfur, homopolymer None. Resorcinol Formaldehyde Resin None. N-1,3-Dimethylbutyl-N'-Phenyl-P-Phenylenediamine None. 2-(Morpholinothio)Benzothiazole None. di(Benzothiazol-2-yl) Disulphide None. ACGIH TLV (United States, 3/2020). Resorcinol TWA: 10 ppm 8 hours. TWA: 45 mg/m<sup>3</sup> 8 hours. STEL: 20 ppm 15 minutes. STEL: 90 mg/m<sup>3</sup> 15 minutes. NIOSH REL (United States, 10/2016). TWA: 10 ppm 10 hours. TWA: 45 mg/m<sup>3</sup> 10 hours. STEL: 20 ppm 15 minutes. STEL: 90 mg/m<sup>3</sup> 15 minutes. ACGIH TLV (United States, 3/2019). Skin Neodecanoic acid, cobalt salt sensitizer. Inhalation sensitizer. TWA: 0.02 mg/m³, (as Co) 8 hours.

#### **Canada**

#### Occupational exposure limits

Ingredient name	Exposure limits
Carbon black	CA British Columbia Provincial (Canada, 1/2020).  TWA: 3 mg/m³ 8 hours. Form: Inhalable CA Ontario Provincial (Canada, 6/2019).  TWA: 3 mg/m³ 8 hours. Form: Inhalable particulate matter.  CA Alberta Provincial (Canada, 6/2018).  8 hrs OEL: 3.5 mg/m³ 8 hours.  CA Quebec Provincial (Canada, 7/2019).  TWAEV: 3.5 mg/m³ 8 hours.  CA Saskatchewan Provincial (Canada, 7/2013).  STEL: 7 mg/m³ 15 minutes.  TWA: 3.5 mg/m³ 8 hours.
Silica gel, pptd., crystfree	CA British Columbia Provincial (Canada, 1/2020).  TWA: 1.5 mg/m³ 8 hours. Form: Respirable CA Quebec Provincial (Canada, 7/2019).  TWAEV: 6 mg/m³ 8 hours. Form: Respirable dust.  CA Saskatchewan Provincial (Canada, 7/2013).  STEL: 20 mg/m³ 15 minutes.  TWA: 10 mg/m³ 8 hours.
Extracts (Petroleum), Heavy Paraffinic Distillate Solvent	CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 5 mg/m³ 8 hours. Form: Mist 15 min OEL: 10 mg/m³ 15 minutes. Form:



## Section 8. Exposure controls/personal protection

Zinc oxide

Resorcinol

Neodecanoic acid, cobalt salt

Mist

CA Quebec Provincial (Canada, 7/2019).

TWAEV: 5 mg/m<sup>3</sup> 8 hours. Form: mist STEV: 10 mg/m<sup>3</sup> 15 minutes. Form: mist

CA Alberta Provincial (Canada, 6/2018).

8 hrs OEL: 2 mg/m<sup>3</sup> 8 hours. Form:

Respirable

15 min OEL: 10 mg/m³ 15 minutes. Form:

Respirable

CA British Columbia Provincial (Canada, 1/2020).

TWA: 2 mg/m³ 8 hours. Form: Respirable STEL: 10 mg/m³ 15 minutes. Form:

Respirable

CA Saskatchewan Provincial (Canada, 7/2013).

STEL: 10 mg/m<sup>3</sup> 15 minutes. Form:

Respirable dust and fume.

TWA: 2 mg/m³ 8 hours. Form: Respirable

dust and fume.

CA Ontario Provincial (Canada, 6/2019).

TWA: 2 mg/m³ 8 hours. Form: Respirable particulate matter

STEL: 10 mg/m<sup>3</sup> 15 minutes. Form:

Respirable particulate matter

CA Quebec Provincial (Canada, 7/2019).

TWAEV: 5 mg/m³ 8 hours. Form: fume STEV: 10 mg/m³ 15 minutes. Form: fume

CA Alberta Provincial (Canada, 6/2018).

15 min OEL: 90 mg/m<sup>3</sup> 15 minutes.

8 hrs OEL: 10 ppm 8 hours. 8 hrs OEL: 45 mg/m³ 8 hours. 15 min OEL: 20 ppm 15 minutes.

CA British Columbia Provincial (Canada, 1/2020).

TWA: 10 ppm 8 hours. STEL: 20 ppm 15 minutes.

CA Ontario Provincial (Canada, 6/2019).

TWA: 10 ppm 8 hours. STEL: 20 ppm 15 minutes.

CA Quebec Provincial (Canada, 7/2019).

TWAEV: 10 ppm 8 hours. TWAEV: 45 mg/m³ 8 hours. STEV: 20 ppm 15 minutes. STEV: 90 mg/m³ 15 minutes.

CA Saskatchewan Provincial (Canada, 7/2013).

STEL: 20 ppm 15 minutes. TWA: 10 ppm 8 hours.

CA Ontario Provincial (Canada, 1/2018).

TWA:  $0.02 \text{ mg/m}^3$ , (as Co) 8 hours. Form:

Inorganic

CA British Columbia Provincial (Canada, 5/2019). Skin sensitizer. Inhalation sensitizer.



### Section 8. Exposure controls/personal protection

TWA: 0.02 mg/m³, (as Co, Total) 8 hours. CA Quebec Provincial (Canada, 1/2014). Skin sensitizer.

TWAEV: 0.02 mg/m³, (as Co) 8 hours. CA Saskatchewan Provincial (Canada, 7/2013).

STEL: 0.06 mg/m³, (measured as Co) 15 minutes.

TWA: 0.02 mg/m³, (measured as Co) 8 hours.

## Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

## Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

#### **Individual protection measures**

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### **Eye/face protection**

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with sideshields.

## Skin protection Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

#### **Body protection**

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.





## Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### **Appearance**

**Physical state** : Solid. [Opaque.]

Color : Black. Odor : None.

Odor threshold Not applicable. pН : Not available. Melting point/freezing point : Not available. Boiling point, initial boiling : Not available. point, and boiling range

Flash point : Not applicable. **Evaporation rate** : Not available. **Flammability** : Not available. : Not applicable. Lower and upper explosion

limit/flammability limit

Vapor pressure : Not available. Relative vapor density Not applicable. Relative density : Not available. Solubility : Not available. : Not available. Solubility in water Miscible with water : Not available. Partition coefficient: n-

octanol/water

: Not applicable.

**Auto-ignition temperature** : Not applicable. **Decomposition temperature** : Not available. **Viscosity** : Not applicable. Flow time (ISO 2431) : Not available.

Particle characteristics

Median particle size : Not available.

### Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** : No specific data.

**Incompatible materials** : Reactive or incompatible with the following materials: oxidizing materials.

**Hazardous decomposition** products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.





## Section 11. Toxicological information

### Information on toxicological effects

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Carbon black	LD50 Oral	Rat	>15400 mg/kg	-
N-1,3-Dimethylbutyl-N'-	LD50 Dermal	Rabbit	2806 mg/kg	-
Phenyl-P-Phenylenediamine				
	LD50 Oral	Rat	271 mg/kg	-
2-(Morpholinothio)	LD50 Oral	Rat	12560 mg/kg	-
Benzothiazole				
di(Benzothiazol-2-yl)	LD50 Dermal	Rabbit	>7940 mg/kg	-
Disulphide				
	LD50 Oral		>12 g/kg	-
Resorcinol	LD50 Dermal		3360 mg/kg	-
	LD50 Oral	Rat	202 mg/kg	-

#### **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-(Morpholinothio) Benzothiazole	Eyes - Mild irritant	Rabbit	-	50 mg	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 100	-
				mg	
	Eyes - Moderate irritant	Rabbit	-	100 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 500	-
				mg	
	Skin - Mild irritant	Rabbit	-	0.5 g	-
Resorcinol	Eyes - Severe irritant	Rabbit	-	100 mg	-
	Skin - Moderate irritant	Rabbit	_	24 hours 20	-
				mg	
	Skin - Severe irritant	Rabbit	-	500 mg	-

#### **Sensitization**

There is no data available.

#### **Mutagenicity**

There is no data available.

#### **Carcinogenicity**

#### **Classification United States**

Product/ingredient name	OSHA	IARC	NTP
Carbon black	-	2B	-
Silica gel, pptd., crystfree	-	3	-
Resorcinol	-	3	-
Neodecanoic acid, cobalt salt	-	2B	Reasonably anticipated to be a human carcinogen.

#### **Classification Canada**

Product/ingredient name	IARC	NTP	ACGIH
Carbon black	2B	-	A3
Silica gel, pptd., crystfree	3	-	-
Resorcinol	3	-	A4
Neodecanoic acid, cobalt salt	2B	Reasonably anticipated to be a human carcinogen.	A3





## **Section 11. Toxicological information**

#### Reproductive toxicity

There is no data available.

#### **Teratogenicity**

There is no data available.

#### Specific target organ toxicity (single exposure)

There is no data available.

#### Specific target organ toxicity (repeated exposure)

There is no data available.

#### **Aspiration hazard**

There is no data available.

Information on the likely

routes of exposure

: Routes of entry anticipated: Dermal.

#### Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

**Skin contact**: May cause an allergic skin reaction.

**Ingestion**: No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

Eye contactInhalationNo known significant effects or critical hazards.Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

**Skin contact**: Adverse symptoms may include the following:

irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

**Ingestion** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

#### Delayed and immediate effects and also chronic effects from short and long term exposure

#### **Short term exposure**

**Potential immediate**: No known significant effects or critical hazards.

effects

Potential delayed effects : No known significant effects or critical hazards.

Long term exposure

Potential immediate : No known significant effects or critical hazards.

effects

Potential delayed effects : No known significant effects or critical hazards.

#### Potential chronic health effects





## Section 11. Toxicological information

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to

very low levels.

**Carcinogenicity** : May cause cancer. Risk of cancer depends on duration and level of exposure.

**Mutagenicity**: No known significant effects or critical hazards.

**Reproductive toxicity**: May damage fertility or the unborn child.

#### **Numerical measures of toxicity**

#### **Acute toxicity estimates**

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)		Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/ I)
Premium Range Tie Gum (Group 1,2,7,8,10 & 12)	22492.1	N/A	N/A	N/A	N/A
Resorcinol Formaldehyde Resin	500	N/A	N/A	N/A	N/A
N-1,3-Dimethylbutyl-N'-Phenyl-P-Phenylenediamine	500	2806	N/A	N/A	N/A
2-(Morpholinothio)Benzothiazole	12560	N/A	N/A	N/A	N/A
Resorcinol	500	3360	N/A	N/A	N/A
Neodecanoic acid, cobalt salt	500	N/A	N/A	N/A	N/A

## Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Carbon black	Acute EC50 37.563 mg/L Fresh water	n water Daphnia - Daphnia magna - Neonate	
Zinc oxide	Acute IC50 1.85 mg/L Marine water Acute IC50 46 μg/L Fresh water	Algae - Skeletonema costatum Algae - Pseudokirchneriella subcapitata - Exponential growth phase	96 hours 72 hours
	Acute LC50 98 μg/L Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 1.1 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
Resorcinol	Acute LC50 78000 μg/L Marine water	Crustaceans - Palaemonetes pugio	48 hours
	Acute LC50 >100000 μg/L Fresh water Acute LC50 40 mg/L Fresh water	Daphnia - Daphnia pulicaria Fish - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling)	48 hours 96 hours

#### Persistence and degradability

There is no data available.

#### **Bioaccumulative potential**





## **Section 12. Ecological information**

Product/ingredient name	LogPow	BCF	Potential
Zinc oxide	-	28960	high
N-1,3-Dimethylbutyl-N'-	2.46	17	low
Phenyl-P-Phenylenediamine			
2-(Morpholinothio)	3.4	-	low
Benzothiazole			
di(Benzothiazol-2-yl)	4.5	1.4 to 51	low
Disulphide			
Resorcinol	0.8	3.16	low
Neodecanoic acid, cobalt salt	-	15600	high

#### **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

## Section 13. Disposal considerations

#### **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## **Section 14. Transport information**

	DOT Classification	TDG Classification	IMDG	IATA
UN number	UN3077	UN3077	UN3077	UN3077
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (N- 1,3-Dimethylbutyl-N'-Phenyl-P- Phenylenediamine)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (N- 1,3-Dimethylbutyl-N'-Phenyl-P- Phenylenediamine)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (N- 1,3-Dimethylbutyl-N'-Phenyl-P- Phenylenediamine)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (N- 1,3-Dimethylbutyl-N'-Phenyl-P- Phenylenediamine)
Transport hazard class(es)	9	9	9	9
Packing group	III	III	III	III
Environmental hazards	Yes.	Yes.	Yes.	Yes.

**AERG** : 171

#### **Additional information**





## Section 14. Transport information

**DOT Classification** 

: Non-bulk packages of this product are not regulated as hazardous materials unless transported by inland waterway. This product is not regulated as a hazardous material when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of §§ 173.24 and 173.24a.

**TDG Classification** 

: Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.43-2.45 (Class 9), 2.7 (Marine pollutant mark). Non-bulk packages of this product are not regulated as dangerous goods when

transported by road or rail.

**IMDG** 

This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

**IATA** 

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to IMO instruments

## **Section 15. Regulatory information**

U.S. Federal regulations

: TSCA 8(a) CDR Exempt/Partial exemption: Not determined Clean Water Act (CWA) 307: Zinc oxide; Benzo[a]pyrene Clean Water Act (CWA) 311: Resorcinol; p-Cresol; Formaldehyde

**Clean Air Act Section 112** 

(b) Hazardous Air **Pollutants (HAPs)**  : Listed

Clean Air Act Section 602

Class I Substances

: Not listed

Clean Air Act Section 602

Class II Substances

: Not listed

**DEA List I Chemicals** (Precursor Chemicals)

**DEA List II Chemicals** 

: Not listed

: Not listed

(Essential Chemicals)

#### **SARA 302/304**

#### Composition/information on ingredients

			SARA 302 TPQ		SARA 304 RQ	
Name	%	EHS	(lbs)	(gallons)	(lbs)	(gallons)
Formaldehyde	≤0.0025	Yes.	500	73.9	100	14.8

**SARA 304 RQ** : 5120327.7 lbs / 2324628.8 kg

**SARA 311/312** 



## **Section 15. Regulatory information**

: SKIN SENSITIZATION - Category 1 Classification

CARCINOGENICITY - Category 1B

TOXIC TO REPRODUCTION - Category 1B

#### **Composition/information on ingredients**

Name	%	Classification
Extracts (Petroleum), Heavy Paraffinic Distillate Solvent	≥5 - ≤10	CARCINOGENICITY - Category 1B
Sulfur, homopolymer	≥1 - ≤3	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
Resorcinol Formaldehyde Resin	≥1 - ≤3	ACUTE TOXICITY (oral) - Category 4
		SKIN CORROSION/IRRITATION - Category 2
		SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
N-1,3-Dimethylbutyl-N'-Phenyl-P-	≥0.3 - <1	ACUTE TOXICITY (oral) - Category 4
Phenylenediamine		SKIN SENSITIZATION - Category 1
		TOXIC TO REPRODUCTION - Category 1B
2-(Morpholinothio)Benzothiazole	≥0.3 - <1	SKIN CORROSION/IRRITATION - Category 2
		SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
		SKIN SENSITIZATION - Category 1
di(Benzothiazol-2-yl) Disulphide	≥0.3 - ≤1	SKIN SENSITIZATION - Category 1
Neodecanoic acid, cobalt salt	≤0.3	ACUTE TOXICITY (oral) - Category 4
		SKIN SENSITIZATION - Category 1
		TOXIC TO REPRODUCTION (Fertility) - Category 2

#### **SARA 313**

	Product name	CAS number	%
Form R - Reporting requirements			≥1 - ≤3 ≤0.3
Supplier notification		1314-13-2 27253-31-2	≥1 - ≤3 ≤0.3

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

#### State regulations

**Massachusetts** 

: The following components are listed: Carbon black; Silica gel, pptd., cryst.-free; Extracts (Petroleum), Heavy Paraffinic Distillate Solvent; Zinc oxide

**New York** 

: None of the components are listed.

**New Jersey** 

: The following components are listed: Carbon black; Silica gel, pptd., cryst.-free; Extracts (Petroleum), Heavy Paraffinic Distillate Solvent; Zinc oxide

**Pennsylvania** 

: The following components are listed: Carbon black; Silica gel, pptd., cryst.-free; Zinc oxide

#### California Prop. 65



⚠ WARNING: This product can expose you to chemicals including Formaldehyde and Benzo[a]pyrene, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

	No significant risk level	Maximum acceptable dosage level
,	Yes. Yes.	-

#### **Canadian lists**

**Canadian NPRI** : The following components are listed: Zinc oxide; Neodecanoic acid, cobalt salt

**CEPA Toxic substances** : The following components are listed: chlorinated alkanes



## **Section 15. Regulatory information**

#### International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### **Montreal Protocol**

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

#### **Inventory list**

Canada : At least one component is not listed.United States (TSCA 8b) : At least one component is not listed.

#### Section 16. Other information

#### Procedure used to derive the classification

Classification	Justification
SKIN SENSITIZATION - Category 1	Calculation method
CARCINOGENICITY - Category 1	Calculation method
TOXIC TO REPRODUCTION - Category 1	Calculation method
AQUATIC HAZARD (ACUTE) - Category 2	Calculation method
AQUATIC HAZARD (LONG-TERM) - Category 2	Calculation method

#### **History**

Date of issue/Date of : 01/30/2022

revision

Date of previous issue : 11/30/2018

Version : 4

Prepared by : KMK Regulatory Services Inc.

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available

SGG = Segregation Group

UN = United Nations

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

